



HYPEROX
AITiN

HYPEROLOX



Hyperlox is the AlTiN coating for cutting applications with **very low internal stress**. This coating is performed with **magnetron sputtering technology**, designed to achieve **high adhesion** while **maintaining high hardness values** as well as **excellent resistance to oxidation at high temperatures**. The deposition technology also guarantees the absence of droplets and optimum coating roughness.

MAIN APPLICATION

- Milling and drilling of hardened steel and titanium
- Medical micro tools

COATING PROPERTIES

VISUAL FEATURES

Surface



Values	Measurement parameters of color According to ISO11664-4
40 ÷ 50	L* Brightness
0 ÷ 3	a* Color coordinate
-3 ÷ 0	b* Color coordinate

NOTES:

Non-functional requirement, indicative values

PHYSICAL FEATURES

Measure	Values	Measurement
Coating thickness*	1 ÷ 7 µm	Calotest on sample
Coating hardness***	2600 ± 200 HV	Nanoindentation 20mN/20s
Roughness Ra**	0,03 ÷ 0,08 µm	From sample with Ra < 0,03µm
Coefficient of friction**	0,6 ÷ 1,0	Pin on disk, dry, against Al ₂ O ₃

NOTES:

- * depends on the application.
- ** depends on the test conditions.

TECHNOLOGICAL FEATURES

Coating technology	Magnetron sputtering
Chemical composition	AlTiN
Structure	Single layer
Coating temperature	450°C
Maximum working temperature	900°C
Biocompatibility	Non-cytotoxic according to ISO10993-5:2009
Food compatibility	-